

STARTER CABLES

BRASS SOLID CLAMPS

REF.	Ø CABLE	LENGTH	A	SECTION				
51238	17mm	5m	700	70mm <sup>2</sup>	4.95	-	2	84
51239	15mm	7m	700	70mm <sup>2</sup>	5.90	-	2	72

BRASS CLAMPS

REF.	Ø CABLE	LENGTH	A	SECTION				
52069	11mm	2,5m	250	25mm <sup>2</sup>	1.55	-	10	240
52070	12mm	3m	350	35mm <sup>2</sup>	1.95	-	5	160
52071	13mm	3m	500	50mm <sup>2</sup>	2.35	-	5	90

BRASS SOLID CLAMPS WITH OVERLOAD PROTECTOR

REF.	Ø CABLE	LENGTH	A	SECTION				
51363	12mm	3m	350	35mm <sup>2</sup>	2.63	-	5	120
51365	12mm	3m	600	50mm <sup>2</sup>	3.10	-	5	90



REF.	DESCRIPTION				
14145	STARTER CABLE COPPER CLIPS	0.20	-	30	-
14146	STARTER CABLE COPPER CLIPS	0.20	-	30	1920
14147	SOLID BRASS BOOSTER CLAMPS	0.35	-	15	-
14148	SOLID BRASS BOOSTER CLAMPS	0.35	-	15	-

**53687**

11.35 - 1 14

370mm 370mm 209mm

JUMP STARTER 12V

- Voltage: 12V.
- Battery: 222Ah Lead-acid battery (1PCS).
- Starting current: 750A.
- Peak current: 1500A.

12V 9,5 Kg. 6-40H

12V DC 15A

230V 50Hz x1 12V 1A



SPARE PARTS AVAILABLE

- A INTERNAL BATTERY VOLTAGE STATUS
- B INTERNAL BATTERY VOLTAGE TEST BUTTON
- C ON/OFF SWITCH
- D BUILT-IN LED LIGHT: INCREASES THE WORKING AREA VISIBILITY

**53688**

18.05 - 1 14

370mm 370mm 209mm

JUMP STARTER 12/24V

- Voltage: 12V/24V.
- Battery: 22Ah Lead-acid battery AGM (2PCS).
- Starting current: 12V: 1500A/3000A.
- Peak current: 24V: 750A/1500A.
- Battery charging time:
- Battery completely empty: 8 hours
- Battery level at 10-20%: 4 hours

12V 24V 16,3 Kg. 6-40H

12V DC 15A

230V 50Hz x1 12V 1A



SPARE PARTS AVAILABLE

- A INTERNAL BATTERY VOLTAGE STATUS
- B INTERNAL BATTERY VOLTAGE TEST BUTTON
- C ON/OFF SWITCH
- D BUILT-IN LED LIGHT: INCREASES THE WORKING AREA VISIBILITY