

Battery electric vane self-priming pump 12 or 24V direct electricity, constituted by cast iron body, sintered steel impeller and acetyl resin vane. Built-in by-pass valve and stainless steel filter.



Battery electric pump 45 l for diesel transfer equipped with:

Power cable 2 m length sec. 2,5 mmq with pincers and fuse

Power cable 4 m length sec. 4 mmq with pincers and fuse

Self-priming rotary electric pump

Cast iron body

By-pass valve

DC engine

Stainless steel filter 100 micron

Motor protection rating IP55

| Ref. | Flow rate | Voltage | Power | Electricity | Cable length | Inlet-Outlet | Duty cycle | Max suction height | Weight | Packaging |
|------|-----------|---------|-------|-------------|--------------|--------------|------------|--------------------|--------|-----------|
| | l/min | DC Volt | W | A | m | BSPG | min | m | kg | mm |

| | | | | | | | | | | |
|---------------------|-----------|----|-----|----|---|-----------|----|---|------|-------------|
| 091-5080-045 | 45 | 12 | 264 | 18 | 2 | F 1"-F 1" | 40 | 3 | 5,10 | 250X195X210 |
| 091-5081-045 | 45 | 12 | 264 | 18 | 4 | F 1"-F 1" | 40 | 3 | 5,10 | 250X195X210 |
| 091-5082-045 | 45 | 24 | 312 | 10 | 2 | F 1"-F 1" | 40 | 3 | 5,10 | 250X195X210 |
| 091-5083-045 | 45 | 24 | 312 | 10 | 4 | F 1"-F 1" | 40 | 3 | 5,10 | 250X195X210 |

Dimensions:

