## **ELECTRIC PUMPS FOR DIESEL FUEL TRANSFER**



Electric pump 115 o 230V, volumetric self-primig vane. They are equipped with asynchronous induction self-ventilated engine with motor protection rating IP55, insulaton class type F, internal protection. Built-in by-pass valve and stailess steel filter.



## Electric pump 100 I for diesel fuel transfer equipped with:

Power cable 2 m lenght, Schuko plug Self-priming rotary electric pump Cast iron body By-pass valve AC engine Stainless steel filter 100 micron Motor protection rating IP55

| R | ef. | Flow rate | Voltage  | Power | Electri-<br>city | Cable<br>lenght | Inlet-outlet | Duty cycle | Weight | Packaging |
|---|-----|-----------|----------|-------|------------------|-----------------|--------------|------------|--------|-----------|
|   |     | l/min     | AC V./Hz | W     | А                | m               | BSPG         | min        | kg     | mm        |

| 091-5100-100 | 100 | 230/50 | 805 | 4,5 | 2 | F 1"-F 1" | Contin. | 14,00 | 300X215X230 |
|--------------|-----|--------|-----|-----|---|-----------|---------|-------|-------------|
|--------------|-----|--------|-----|-----|---|-----------|---------|-------|-------------|

| 091-5101-100 | <b>100</b> 1 | 115/60 977 | 8,5 | 2 | F 1"-F 1" | Contin. | 14,00 | 300X215X230 |
|--------------|--------------|------------|-----|---|-----------|---------|-------|-------------|
|--------------|--------------|------------|-----|---|-----------|---------|-------|-------------|

## **Dimensions:**

