

## Art. 024-1233-A00

### Oil digital dispensing nozzle

Composed by:

Oil digital flow meter (Art.024-1234-000)

Rubber protection

Handle with F 1/2" swivel joint

**Flexible end 105°**

Manual drop valve Ø 12 mm



024-1233-A00

## Art. 024-1233-B00

### Oil digital dispensing nozzle

Composed by:

Oil digital flow meter (Art.024-1234-000)

Rubber protection

Handle with F 1/2" swivel joint

**Rigid end 45°**

Manual drop valve Ø 12 mm



024-1233-B00

## Art. 024-1233-C00

### Oil digital dispensing nozzle

Composed by:

Oil digital flow meter (Art.024-1234-000)

Rubber protection

Handle with F 1/2" swivel joint

**Flexible end 105°**

Automatic drop valve Ø 14 mm



024-1233-C00

## Art. 024-1233-D00

### Oil digital dispensing nozzle

Composed by:

Oil digital flow meter (Art.024-1234-000)

Rubber protection

Handle with F 1/2" swivel joint

**Rigid end 45°**

Automatic drop valve Ø 14 mm



024-1233-D00

## Art. 024-1234-000

### Oil digital flow meter

It is equipped with two displays, one for partial measures (rekitable) and one for total measures (not rekitable) of the dispensed fluid



024-1234-000

Technical Data	023-1234-000
Inlet/outlet connection	F 1/2" BSP
Pressure min/max	0,35 - 70 bar
Flow min/max	1 - 30 l/min
Temperature	-10° + 50° C
Accuracy	+/- 0,5%
Lithium battery	2 x 1,5V AAA

## FEATURES

- Easy calibration
- Double totalizer
- Electronic rekit
- High precision
- Ergonomic grip
- Button to block the lever
- Low battery consumption
- Different units of measurements can be selected: litres, pints, quarts or gallons.
- Not approved for public usage