



**024-1243-A00**

### Art. 024-1243-A00

**Recalibrating oil digital dispensing nozzle**

Composed by:

Oil digital flow meter (Art.024-1246-000)

Rubber protection

Handle with F 1/2" swivel joint

**Flexible end 105°**

Manual drop valve Ø 12 mm



**024-1243-B00**

### Art. 024-1243-B00

**Recalibrating oil digital dispensing nozzle**

Composed by:

Oil digital flow meter (Art.024-1246-000)

Rubber protection

Handle with F 1/2" swivel joint

**Rigid end 45°**

Manual drop valve Ø 12 mm



**024-1243-C00**

### Art. 024-1243-C00

**Recalibrating oil digital dispensing nozzle**

Composed by:

Oil digital flow meter (Art.024-1246-000)

Rubber protection

Handle with F 1/2" swivel joint

**Flexible end 105°**

Automatic drop valve Ø 14 mm



**024-1243-D00**

### Art. 024-1243-D00

**Recalibrating oil digital dispensing nozzle**

Composed by:

Oil digital flow meter (Art.024-1246-000)

Rubber protection

Handle with F 1/2" swivel joint

**Rigid end 45°**

Automatic drop valve Ø 14 mm



**024-1246-000**

### Art. 024-1246-000

**Recalibrating oil digital flow meter**

It is equipped with two displays, one for partial measures (rekittable) and one for total measures (not-rekittable) of the dispensed fluid

## FEATURES

- Easy calibration
- Double totalizer
- Electronic rekit
- High precision
- Ergonomic grip
- Button to block the lever
- Low battery consumption
- Different units of measurements can be selected: litres, pints, quarts or gallons.
- Not approved for public usage

Technical Data	024-1246-000
Inlet/outlet connection	F 1/2" BSP
Pressure min/max	0,35 - 100 bar
Flow min/max	1 - 35 l/min
Temperature	-10° + 50° C
Accuracy	+/- 0,5%
Lithium battery	1 x 3V CR123A