



**024-1251-000**

**Art. 024-1251-000**

Oil digital flow meter high delivery

Flow rate **60 l/min**

It is equipped with two displays, one for partial measures (rekittable) to 5 digits and one for total measures (notrekittable) to 8 digits of the dispensed fluid



**092-5130-000**

**Art. 092-5130-000**

Digital flow meter with gears MGE-110

min-max flow rate **5-110 l/min** (lubricants)

6 digits totalizer (non rekittable)

6 digits partial (rekittable)

Allowed fluids: diesel, oil



**092-5140-000**

**Art. 092-5140-000**

Digital flow meter with gears MGE-250

min-max flow rate **10-150 l/min** (lubricants)

6 digits totalizer (non rekittable)

6 digits partial (rekittable)

Allowed fluids: diesel, oil



**092-5150-000**

**Art. 092-5150-000**

Digital flow meter with gears MGE-400

min-max flow rate **15-300 l/min** (lubricants)

6 digits totalizer (non rekittable)

6 digits partial (rekittable)

Allowed fluids: diesel, oil

Technical Data	024-1251-000	092-5130-000	092-5140-000	092-5150-000
Inlet/outlet connection	F 3/4"-1" BSP	F 1" BSP	F 1.1/2" BSP	F 2" BSP
Pressure min/max	1 - 70 bar	1 - 55 bar	1 - 50 bar	1 - 50 bar
Flow min/max	6 - 60 l/m	5 - 110 l/m	10 - 150 l/m	15 - 300 l/m
Temperature	-10° + 50° C	-10° + 50° C	-10° + 50° C	-10° + 5 0° C
Accuracy	+/- 0,5%	+/- 0,5%	+/- 0,5%	+/- 0,5%
Lithium battery	2 x 1,5V AAA	1 x 3V CR 2450N	1 x 3V CR 2450N	1 x 3V CR 2450N

The digital flow meters allow to show correctly the push-button delivery, equipped with two displays, one for partial measures rekittable and one for total measures not rekittable that underline the dispensed fluid. Suitable for different type of oils, low, medium or high viscosity.