



025-1272-000



025-1274-000

Art. 025-1272-000

Connection 1" G - M40X1,25

It connects the pump to the modular extensions

Art. 025-1274-000

Connection M 40X1,25

Allow the connection between the modular extensions

Art. 025-1275-025

Ø 42 mm 250 mm length extension

Thread F-F M 40X1,25

Art. 025-1275-050

Ø 42 mm 500 mm length extension

Thread F-F M 40X1,25

Art. 025-1275-092

Ø 42 mm 912 mm length extension

Thread F-F M 40X1,25

Art. 025-1275-122

Ø 42 mm 1212 mm length extension

Thread F-F M 40X1,25

Art. 025-1276-000

Oil shank end with filter Ø 42 mm

Thread M 40X1,25

025-1276-000



025-1275-025



025-1275-050



025-1275-092



025-1275-122



R18-1250-006



R18-1251-006

Stainless steel 90° connection

| Article | Inlet-Outlet | Max pressure | Metal | Weight |
|--------------|--------------|--------------|-------------|----------|
| R18-1250-006 | M1"- F1" | 100 bar | SS AISI 316 | 0,137 kg |
| R18-1251-006 | F1"- F1" | 100 bar | SS AISI 316 | 0,158 kg |

Stainless steel connection fixed rubber hose

| Article | Inlet | Ø hose | Metal | Weight |
|--------------|-------|--------|-------------|----------|
| R18-0821-256 | M1" | 25 mm | SS AISI 316 | 0,137 kg |

Y-shaped nickel-plated brass in-line filter

| Article | Inlet | Ø hose | Metal | Weight |
|--------------|-------|--------|-------|----------|
| R18-0855-255 | M3/4" | 25 mm | Brass | 0,084 kg |
| R18-0855-206 | M1" | 20 mm | Brass | 0,095 kg |
| R18-0855-256 | M1" | 25 mm | Brass | 0,126 kg |

Stainless steel connection fixed rubber hose

| Article | Inlet | Ø hose | Metal | Weight |
|--------------|-------|--------|------------------|----------|
| R18-0803-206 | M1" | 20 mm | Galvanized steel | 0,095 kg |
| R18-0803-256 | M1" | 25 mm | Galvanized steel | 0,105 kg |

Y-shaped nickel-plated brass in-line filter

| Article | Inlet-Outlet | Max pressure | Filter | Weight |
|--------------|--------------|--------------|--------|----------|
| R34-0002-004 | F1/2"- F1/2" | 100 bar | 400 µm | 0,160 kg |
| R34-0002-005 | F3/4"- F3/4" | 100 bar | 400 µm | 0,220 kg |
| R34-0002-006 | F1"- F1" | 100 bar | 400 µm | 0,330 kg |



R18-0855-256



R18-0821-256



R18-0803-206



R18-0803-256



R34-0002-006