

Meclube Model A55

Made of ALUMINIUM


Compression ratio: 1:1
 Max flow-rate: 55 l/min
 Fluid connections: 1/2" BSP



EX II 3/3 GD h IIB T4 135°C ATEX zone2

ARTICLE	CASING	DIAPHRAGM	BALLS	GASKET	FLUIDS
028-A055-AB1	ALUMINIUM	HYTREL	SS AISI 316	NBR	oil-exhausted oil-diesel fuel
028-A055-AB2	ALUMINIUM	HYTREL+PTFE	PTFE	VITON	water-anti-freeze-windscreen
028-A055-AB3	ALUMINIUM	HYTREL+PTFE	PTFE	PTFE	aggressive fluids (acids and basics)
028-A055-AB4	ALUMINIUM	SANTOPRENE	EPDM	EPDM	abrasive liquids - alkaline/basic


Performance



The curves and performance values refer to pumps with submerged suction and a free delivery outlet with water at 20°C, and vary according to the construction material.

Technical data

Fluid connections: **1/2" BSP**
 Air connection: **1/4" BSP**
 Max flow-rate: **55 l/min**
 Max air pressure: **8 bar**
 Max delivery head: **80 m**
 Max Suction Lift Dry: **5,0 m**
 Max Suction Lift Wet: **9,8 m**
 Max Solid passing: **3,5 mm**
 Noise level: **70 dB**
 Displacement per cycle: **140 cm³**
 Max Viscosity: **20000 cps**



Dimensions

A55

A (mm) 234
 B (mm) 156
 C (mm) 245
 Gross weight kg 4,61
 MAX Temperature -20°C + 95°C