

# WHEELED ASPIRATORS FOR EXHAUSTED OIL WITH PNEUMATIC PUMP



## Art. 042-1410-000

**Wheeled aspirator with pump for drums of 50-60 l**

Composed by:

Art.020-1165-000 Air-operated pump **ratio=1:1**





Equipped with the flow rate adjuster and the vacuum gauge


Art.030-1395-000 4-wheels trolley

Art.044-1479-000 Set 10 standard probes

2 m aspiration - delivery hoses

Art.024-1232-F00 Oil dispensing nozzle with flexible end

			
042-1410-000	26,700	0,072	1



042-1410-000

## Art. 042-1411-000

**Wheeled aspirator with pump for drums of 180-220 l**

Composed by:

Art.020-1165-000 Air-operated pump **ratio=1:1**





Equipped with the flow rate adjuster and the vacuum gauge


Art.030-1400-000 4-wheels trolley

Art.044-1479-000 Set 10 standard probes

2 m aspiration - delivery hoses

Art.024-1232-F00 Oil dispensing nozzle with flexible end

			
042-1411-000	50,100	0,170	1



042-1411-000

## Art. 042-1412-000

**Air-operated oil suction-drainer 90 l with pneumatic oil pump**

Pneumatic air emptying (max pressure 0,5 bar)

Composed by:

Tank capacity 90 l with level indicator

Abs tool holder basin with 3 sections

Art.020-1165-000 Air-operated pump **ratio=1:1**

Equipped with the flow rate adjuster and the vacuum gauge


Recovery basin capacity 20 l


with ergonomic and **360° swivelling** abs funnel

with breakwater grate to drip the substituted oil filters

Art.044-1479-000 Set 10 standard probes

2 m aspiration - delivery hoses

			
042-1412-000	44,000	0,240	2



042-1412-000

Suitable for the aspiration of exhausted oil and similar fluids from every motor vehicle. When you reverse the position of the two hoses the aspirator can deliver the aspirated fluids.

**Warning:** It is not possible to suck brake oils, fuels, inflammable and corrosive liquids.