WHEELED EXHAUSTED OIL DRAIN UNITS



Art. 045-1470-000

Wheeled exhausted oil drain unit suitable for drums 50-60 I

Composed by:

Art.030-1395-000 4-wheels trolley

Art.049-1477-000 Metal basin 15 I

with breakwater grate to drip the substituted oil filters

Art.025-1260-000 2" G threaded ring for drum connection





Art. 045-1475-000

Wheeled exhausted oil drain unit suitable for barrels 180-220 I

Composed by:

Art.030-1400-000 4-wheels trolley


Art.049-1478-000 Metal basin 20 I

with ergonomic and 360° swivelling abs funnel

with breakwater grate to drip the substituted oil filters

Art.025-1262-000 2" G threaded ring for drum connection





Art. 049-1477-000

15 I recovery basin

Composed by:

Metal basin 15 I

with breakwater grate to drip the substituted oil filters

Ø 30 L 750 mm hose with 3/4" G valve

2" G threaded ring for drum connection

Art. 049-1478-000

20 I recovery basin


Composed by:


Metal basin 20 I


with ergonomic and 360° swivelling abs funnel with breakwater grate to drip the substituted oil filters

Ø 42 L 750 mm hose with 1" G valve

2" G threaded ring for drum connection











049-1475-000



For the recovery by fall of exhausted oil of the engine, the transmission and the differential of motor-vehicles on lifts.

The basin is equipped with a grate of support to drip the substituted filters, and it can be regulated according to the height.

Warning: It is not possible to recovery brake oils, fuels, inflammable and corrosive liquids.