

FIXED AUTOMATIC HOSE REELS IN PAINTED STEEL FOR WATER 150 °C 400 bar

Equipped with:

- Blue no trace synthetic rubber hoses 2SC
- Galvanized steel connections
- AISI 304 stainless steel 90° swivelling joint
- Teflon seals



F-400	Article	L. hose	Ø hose	Max pressure	Inlet-Outlet
	070-1205-300	without hose	-	-	F1/2"G - M3/8"G
	070-1205-400	without hose	-	-	F1/2"G - M1/2"G
	070-1205-210	10 m	5/16"	400 bar	F1/2"G - F3/8"G
	070-1205-215	15 m	5/16"	400 bar	F1/2"G - F3/8"G
	070-1205-310	10 m	3/8"	400 bar	F1/2"G - F3/8"G
	070-1205-410	10 m	1/2"	400 bar	F1/2"G - F1/2"G



F-460	Article	L. hose	Ø hose	Max pressure	Inlet-Outlet
	070-1305-300	without hose	-	-	F1/2"G - M3/8"G
	070-1305-400	without hose	-	-	F1/2"G - M1/2"G
	070-1305-220	20 m	5/16"	400 bar	F1/2"G - F3/8"G
	070-1305-315	15 m	3/8"	400 bar	F1/2"G - F3/8"G
	070-1305-318	18 m	3/8"	400 bar	F1/2"G - F3/8"G
	070-1305-415	15 m	1/2"	400 bar	F1/2"G - F1/2"G



F-550	Article	L. hose	Ø hose	Max pressure	Inlet-Outlet
	070-1405-300	without hose	-	-	F1/2"G - M3/8"G
	070-1405-400	without hose	-	-	F1/2"G - M1/2"G
	070-1405-320	20 m	3/8"	400 bar	F1/2"G - F3/8"G
	070-1405-325	25 m	3/8"	400 bar	F1/2"G - F3/8"G
	070-1405-420	20 m	1/2"	400 bar	F1/2"G - F1/2"G
	070-1405-425	25 m	1/2"	400 bar	F1/2"G - F1/2"G






F-555	Article	L. hose	Ø hose	Max pressure	Inlet-Outlet
	070-1505-300	without hose	-	-	F1/2"G - M3/8"G
	070-1505-400	without hose	-	-	F1/2"G - M1/2"G
	070-1505-330	30 m	3/8"	400 bar	F1/2"G - F3/8"G
	070-1505-430	30 m	1/2"	400 bar	F1/2"G - F1/2"G



F-560	Article	L. hose	Ø hose	Max pressure	Inlet-Outlet
	070-1605-400	without hose	-	-	F1/2"G - M1/2"G
	070-1605-340	40 m	3/8"	400 bar	F1/2"G - F3/8"G
	070-1605-350	50 m	3/8"	400 bar	F1/2"G - F3/8"G
	070-1605-440	40 m	1/2"	400 bar	F1/2"G - F1/2"G

OVERALL DIMENSIONS FIXED VERSION

Mod.	A	B	C	D	E	F	G	H			
F-400	158	120	168	192	95	460	400	435	12,50<19,50	0,084	1
F-460	158	120	168	192	95	490	460	490	16,50<23,00	0,094	1
F-550	200	150	225	270	120	590	550	600	22,00<45,00	0,130	1
F-555	250	200	225	270	170	590	550	600	26,00<53,00	0,150	1
F-560	440	390	225	270	360	590	550	600	33,00<83,00	0,240	1

