

SWIVELLING AUTOMATIC HOSE REELS IN PAINTED STEEL FOR GREASE FROM 275 TO 400 bar

Equipped with:

- Black synthetic rubber hoses 2SC
- Galvanized steel connections
- Galvanized steel 90° swivelling joint
- Polyurethane seals



Article	L. hose	Ø hose	Max pressure	Inlet-Outlet	S-400
071-1207-200	without hose	-	-	M1/4"G - M1/4"G	
071-1207-300	without hose	-	-	M3/8"G - M3/8"G	
071-1207-400	without hose	-	-	M1/2" - M1/2"	
071-1207-110	10 m	1/4"	400 bar	M1/4"G - M1/4"G	
071-1207-115	15 m	1/4"	400 bar	M1/4"G - M1/4"G	
071-1207-310	10 m	3/8"	330 bar	M3/8"G - M3/8"G	
071-1207-410	10 m	1/2"	275 bar	M1/2"G - M1/2"G	

Article	L. hose	Ø hose	Max pressure	Inlet-Outlet	S-460
071-1307-200	without hose	-	-	M1/4"G - M1/4"G	
071-1307-300	without hose	-	-	M3/8"G - M3/8"G	
071-1307-400	without hose	-	-	M1/2"G - M1/2"G	
071-1307-118	18 m	1/4"	400 bar	M1/4"G - M1/4"G	
071-1307-315	15 m	3/8"	330 bar	M3/8"G - M3/8"G	
071-1307-415	15 m	1/2"	275 bar	M1/2"G - M1/2"G	

Article	L. hose	Ø hose	Max pressure	Inlet-Outlet	S-550
071-1407-300	without hose	-	-	M3/8"G - M3/8"G	
071-1407-400	without hose	-	-	M1/2"G - M1/2"G	
071-1407-320	20 m	3/8"	330 bar	M3/8"G - M3/8"G	
071-1407-325	25 m	3/8"	330 bar	M3/8"G - M3/8"G	
071-1407-420	20 m	1/2"	275 bar	M1/2"G - M1/2"G	
071-1407-425	25 m	1/2"	275 bar	M1/2"G - M1/2"G	

Article	L. hose	Ø hose	Max pressure	Inlet-Outlet	S-555
071-1507-300	without hose	-	-	M3/8"G - M3/8"G	
071-1507-400	without hose	-	-	M1/2"G - M1/2"G	
071-1507-330	30 m	3/8"	330 bar	M3/8"G - M3/8"G	
071-1507-430	30 m	1/2"	275 bar	M1/2"G - M1/2"G	

OVERALL DIMENSIONS SWIVELLING VERSION

Mod.	A	B	C	D	E	F	G	H			
S-400	150	120	168	196	95	460	400	550	13,50<20,50	0,084	1
S-460	150	120	168	196	95	490	460	575	17,50<24,00	0,094	1
S-550	200	150	225	270	120	572	550	680	23,00<45,00	0,130	1
S-555	250	200	225	270	170	572	550	680	27,00<54,00	0,150	1

