

FIXED AUTOMATIC HOSE REELS IN AISI 304 STAINLESS STEEL FOR AIR-WATER FROM 20 TO 28 bar

Equipped with:

- Black synthetic rubber hoses R6, Galvanized steel connections
- Brass 90° swivelling joint, Viton® seals



FX-400

Article	L. hose	Ø hose	Max pressure	Inlet-Outlet
070-2201-300	without hose	-	-	F1/2"G - M3/8"G
070-2201-400	without hose	-	-	F1/2"G - M1/2"G
070-2202-212	12 m	5/16"	28 bar	F1/2"G - M1/4"G
070-2202-218	18 m	5/16"	28 bar	F1/2"G - M1/4"G
070-2202-310	10 m	3/8"	28 bar	F1/2"G - M3/8"G
070-2202-315	15 m	3/8"	28 bar	F1/2"G - M3/8"G
070-2202-410	10 m	1/2"	28 bar	F1/2"G - M1/2"G



FX-460

Article	L. hose	Ø hose	Max pressure	Inlet-Outlet
070-2301-300	without hose	-	-	F1/2"G - M3/8"G
070-2301-400	without hose	-	-	F1/2"G - M1/2"G
070-2302-318	18 m	3/8"	28 bar	F1/2"G - M3/8"G
070-2302-320	20 m	3/8"	28 bar	F1/2"G - M3/8"G
070-2302-415	15 m	1/2"	28 bar	F1/2"G - M1/2"G
070-2302-418	18 m	1/2"	28 bar	F1/2"G - M1/2"G



FX-550

Article	L. hose	Ø hose	Max pressure	Inlet-Outlet
070-2401-400	without hose	-	-	F1/2"G - M1/2"G
070-2402-500	without hose	-	-	F1"G - M3/4"G
070-2402-420	20 m	1/2"	28 bar	F1/2"G - M1/2"G
070-2402-425	25 m	1/2"	28 bar	F1/2"G - M1/2"G
070-2402-515	15 m	3/4"	21 bar	F1"G - M3/4"G



FX-555




Article	L. hose	Ø hose	Max pressure	Inlet-Outlet
070-2502-400	without hose	-	-	F1/2"G - M1/2"G
070-2502-500	without hose	-	-	F1"G - M3/4"G
070-2502-600	without hose	-	-	F1"G - M1"G
070-2502-430	30 m	1/2"	28 bar	F1/2"G - M1/2"G
070-2502-520	20 m	3/4"	21 bar	F1"G - M3/4"G
070-2502-615	15 m	1"	20 bar	F1"G - M1"G



FX-560

Article	L. hose	Ø hose	Max pressure	Inlet-Outlet
070-2602-400	without hose	-	-	F1/2"G - M1/2"G
070-2602-500	without hose	-	-	F1"G - M3/4"G
070-2602-600	without hose	-	-	F1"G - M1"G
070-2602-440	40 m	1/2"	28 bar	F1/2"G - M1/2"G
070-2602-530	30 m	3/4"	21 bar	F1"G - M3/4"G
070-2602-540	40 m	3/4"	21 bar	F1"G - M3/4"G
070-2602-620	20 m	1"	20 bar	F1"G - M1"G
070-2602-630	30 m	1"	20 bar	F1"G - M1"G

OVERALL DIMENSIONS FIXED VERSION

Mod.	A	B	C	D	E	F	G	H			
FX-400	158	120	168	192	95	460	400	435	12,50<19,50	0,084	1
FX-460	158	120	168	192	95	490	460	490	16,50<23,00	0,094	1
FX-550	200	150	225	270	120	590	550	600	22,00<45,00	0,130	1
FX-555	250	200	225	270	170	590	550	600	26,00<53,00	0,150	1
FX-560	440	390	225	270	360	590	550	600	33,00<83,00	0,240	1

