

AUTOMATIC HOSE REELS VARNISHED SWIVELLING FOR GREASE 600 bar



Equipped with:

- Synthetic black rubber hoses 2SC
- Galvanized connections
- Swivelling joint 90° galvanized
- Polyurethane seals

| Article | Hose length | Ø hose | Inlet-outlet |
|--------------|--------------|--------|-----------------|
| 071-1207-200 | Without hose | - | M1/4"G - M1/4"G |
| 071-1207-300 | Without hose | - | M3/8"G - M3/8"G |
| 071-1207-110 | 10 m | 1/4" | M1/4"G - M1/4"G |
| 071-1207-115 | 15 m | 1/4" | M1/4"G - M1/4"G |
| 071-1207-310 | 10 m | 3/8" | M3/8"G - M1/4"G |

S-400



| | | | |
|--------------|--------------|------|-----------------|
| 071-1307-200 | Without hose | - | M1/4"G - M1/4"G |
| 071-1307-300 | Without hose | - | M3/8"G - M3/8"G |
| 071-1307-118 | 18 m | 1/4" | M1/4"G - M1/4"G |
| 071-1307-315 | 15 m | 3/8" | M3/8"G - M1/4"G |

S-460



| | | | |
|--------------|--------------|------|-----------------|
| 071-1407-300 | Without hose | - | M3/8"G - M3/8"G |
| 071-1407-320 | 20 m | 3/8" | M3/8"G - M1/4"G |
| 071-1407-325 | 25 m | 3/8" | M3/8"G - M1/4"G |

S-550



| | | | |
|--------------|--------------|------|-----------------|
| 071-1507-300 | Without hose | - | M3/8"G - M3/8"G |
| 071-1507-330 | 30 m | 3/8" | M3/8"G - M1/4"G |

S-555



OVERALL DIMENSIONS SWIVELLING

| Mod. | A | B | C | D | E | F | G | H | | | |
|-------|-----|-----|-----|-----|-----|-----|-----|-----|-------------|-------|---|
| S-400 | 150 | 120 | 168 | 196 | 95 | 450 | 400 | 510 | 13,50<20,50 | 0,046 | 1 |
| S-460 | 150 | 120 | 168 | 196 | 95 | 480 | 460 | 575 | 17,50<24,00 | 0,060 | 1 |
| S-550 | 200 | 150 | 225 | 270 | 120 | 590 | 550 | 680 | 23,00<45,00 | 0,085 | 1 |
| S-555 | 250 | 200 | 225 | 270 | 170 | 590 | 550 | 680 | 27,00<54,00 | 0,100 | 1 |

