

FOR OIL 160 bar

Equipped with:

- Synthetic black rubber hoses 1SC
- Galvanized connections
- Swivelling joint 90° galvanized
- Polyurethane seals

Article	Hose length	Ø hose	Inlet-outlet
075-4506-400	Without hose	-	M1/2"G - M1/2"G
075-4506-410	10 m	1/2"	M1/2"G - M1/2"G
075-4506-415	15 m	1/2"	M1/2"G - M1/2"G
075-4506-418	18 m	1/2"	M1/2"G - M1/2"G

CS-500



FOR GREASE 600 bar

Equipped with:

- Synthetic black rubber hoses 2SC
- Galvanized connections
- Swivelling joint 90° galvanized
- Polyurethane seals

Article	Hose length	Ø hose	Inlet-outlet
075-4507-200	Without hose	-	M1/4"G - M1/4"G
075-4507-300	Without hose	-	M3/8"G - M3/8"G
075-4507-110	10 m	1/4"	M1/4"G - M1/4"G
075-4507-115	15 m	1/4"	M1/4"G - M1/4"G
075-4507-118	18 m	1/4"	M1/4"G - M1/4"G
075-4507-310	10 m	3/8"	M3/8"G - M3/8"G
075-4507-315	15 m	3/8"	M3/8"G - M3/8"G

CS-500




FOR ANTFREEZE AND WINDSCREEN 20 bar

Equipped with:

- Antistatic black rubber hoses EPDM
- Stainless steel connections AISI 316
- Stainless steel swivelling joint 90° AISI 316
- Viton seals

Article	Hose length	Ø hose	Inlet-outlet
075-4509-400	Without hose	-	M1/2"G - M1/2"G
075-4509-410	10 m	1/2"	M1/2"G - M1/2"G
075-4509-415	15 m	1/2"	M1/2"G - M1/2"G

CS-500



CS-500 23,600<30,550 0,060 1