



**ME-630**

## FOR AIR - WATER 20 bar

Equipped with:

- Swivelling joint 90° nickel-plated brass
- Viton seals

Article	Mod.	Hose reels capacity		Inlet-Outlet
076-8222-600	ME-630	3/4" - 45 m	1" - 30 m	F1"G - M1"G
076-8322-600	ME-640	3/4" - 76 m	1" - 46 m	F1"G - M1"G
076-8422-600	ME-650	3/4" - 91 m	1" - 61 m	F1"G - M1"G



**ME-640**

## FOR WATER 150°C 200 bar

Equipped with:

- Swivelling joint 90° stainless steel AISI 304
- Viton seals

Article	Mod.	Hose reels capacity		Inlet-Outlet
076-8224-600	ME-630	3/8" - 80 m	1/2" - 70 m	F1"G - M1"G
076-8324-600	ME-640	3/8" - 120 m	1/2" - 100 m	F1"G - M1"G
076-8424-600	ME-650	3/8" - 160 m	1/2" - 140 m	F1"G - M1"G

## FOR OIL AND SIMILAR 140 bar

Equipped with:

- Swivelling joint 90° galvanized
- Polyurethane seals

Article	Mod.	Hose reels capacity		Inlet-Outlet
076-8226-600	ME-630	3/4" - 45 m	1" - 30 m	F1"G - M1"G
076-8326-600	ME-640	3/4" - 76 m	1" - 46 m	F1"G - M1"G
076-8426-600	ME-650	3/4" - 91 m	1" - 61 m	F1"G - M1"G



**ME-650**

## FOR GREASE 400 bar

Equipped with:

- Swivelling joint 90° galvanized
- Polyurethane seals

Article	Mod.	Hose reels capacity		Inlet-Outlet
076-8227-600	ME-630	3/8" - 80 m	1/2" - 70 m	F1"G - M1"G
076-8327-600	ME-640	3/8" - 120 m	1/2" - 100 m	F1"G - M1"G
076-8427-600	ME-650	3/8" - 160 m	1/2" - 140 m	F1"G - M1"G




## FOR DIESEL 10 bar

Equipped with:

- Swivelling joint 90° galvanized
- Viton seals

Article	Mod.	Hose reels capacity		Inlet-Outlet
076-8228-600	ME-630	3/4" - 45 m	1" - 30 m	F1"G - M1"G
076-8328-600	ME-640	3/4" - 76 m	1" - 46 m	F1"G - M1"G
076-8428-600	ME-650	3/4" - 91 m	1" - 61 m	F1"G - M1"G

## OVERALL DIMENSIONS

Mod.	A	B	C	D	E	F	G			
ME-630	267	292	610	435	615	511	666	42	0,200	1
ME-640	267	394	610	533	713	511	666	44	0,230	1
ME-650	267	508	610	650	830	511	666	48	0,266	1

