

Specifically designed to temporally connect the cable to the pulling rope. They consist of steel wire which effectively distribute the grip effect on the cable. Also available in open version.



### Socket joint with 2 loops Mod. GCP/GCA

Model		Cable Ø	Net length	Working load	Suitable swivel
Passing	Open	[mm]	[mm]	[kN]	
GCP241	GCA240	10-14	800	6.6	GGT001
GCP252	GCA250	15-20	800	6.6	GGT001
GCP262	GCA260	21-25	800	8.3	GGT001
GCP271	GCA270	26-30	800	10	GGT001
GCP281	GCA280	26-45	1000	16.6	GGT001
GCP292	GCA290	31-40	1000	16.6	GGT001
GCP301	GCA300	41-50	1000	16.6	GGT001
GCP311	GCA310	46-60	1000	16.6	GGT001
GCP326	GCA320	61-80	1000	26.6	GGT001
GCP332	GCA330	81-100	1200	33.3	GGT001
GCP341	GCA340	101-140	1400	33.3	GGT001
GCP351	GCA350	141-170	1400	33.3	GGT001
GCP361	GCA360	171-200	1400	33.3	GGT001

Specifically designed to temporally connect two lengths of cable. They consist of steel wire which effectively distribute the grip effect on the cable.



### Double head type socket joint Mod. GCS

Model	Cable Ø	Net length	Working load
	[mm]	[mm]	[kN]
GCS620	11-14	1200	6.6
GCS630	15-20	1200	6.6
GCS640	21-25	1200	8.3
GCS650	26-30	1200	10
GCS660	26-45	1400	16.6
GCS670	31-40	1400	15
GCS680	41-50	1600	16.6
GCS690	46-60	1600	16.6
GCS700	61-80	1600	26.6
GCS710	81-100	2000	33.3
GCS720	101-140	2400	33.3
GCS730	141-170	2400	33.3
GCS740	171-200	2400	33.3
GCS731	150-180	4000	66.6
GCS741	180-210	4000	66.6

Certified Quality System  
**ISO 9001:2008**

Keep you updated on: [www.tesmec.com](http://www.tesmec.com)

#### Tesmec S.p.A.

Headquarters  
Via Zanica, 17/0 - 24050 Grassobbio (BG) - Italy  
Tel: +39.035.4232911 - Fax: +39.035.4522445

Manufacturing facilities  
Via Pertegalli, 2 - 24060 Endine Gaiano (BG) - Italy  
Tel: +39.035.825024 - Fax: +39.035.826375

Manufacturing facilities  
Via Don Brambilla, 26/28 - 23844 Sironè (LC) - Italy  
Tel: +39.031.858311 - Fax: +39.031.853562

**U 115**