

# COH

## POLYPROPYLENE POLYETHYLENE ROPE

- UV RESISTANT
- WATER PROOFED
- EASILY SPLICED



# COA

## NYLON ROPE

POLYESTER MESH SOCK WITH HIGH STRENGTH  
NYLON CORE

SPECIAL SEWN EYES WITHOUT BREAKING  
LOAD LOSS

COH

COA

### COH

MODEL	DIAMETER	ROPE WEIGHT	ELONGATION WITH 20% OF BREAKING LOAD	BREAKING LOAD	STANDARD LENGTH
<b>COH010</b>	10 mm	0.040 kg/m	7 %	14 kN	1000 m
<b>COH012</b>	12 mm	0.060 kg/m	7 %	23 kN	1000 m
<b>COH014</b>	14 mm	0.075 kg/m	7 %	26 kN	1000 m
<b>COH016</b>	16 mm	0.092 kg/m	7 %	32 kN	1000 m
<b>COH018</b>	18 mm	0.110 kg/m	7 %	40 kN	1000 m
<b>COH020</b>	20 mm	0.150 kg/m	7 %	51 kN	1000 m
<b>COH022</b>	22 mm	0.165 kg/m	7 %	62 kN	1000 m

#### NOTE

Available spliced eye ALC145.

If 2 eyes are needed, 2 ALC145 have to be ordered.

### COA

MODEL	DIAMETER	ROPE WEIGHT	ELONGATION WITH 30% OF BREAKING LOAD	BREAKING LOAD	STANDARD LENGTH
<b>COA006</b>	6 mm	0.028 kg/m	7.5 %	7.5 kN	1000 m
<b>COA008</b>	8 mm	0.046 kg/m	7.5 %	12 kN	1000 m
<b>COA010</b>	10 mm	0.073 kg/m	7.5 %	20 kN	1000 m
<b>COA012</b>	12 mm	0.120 kg/m	7.5 %	35 kN	1000 m
<b>COA014</b>	14 mm	0.145 kg/m	7.5 %	43 kN	1000 m
<b>COA016</b>	16 mm	0.196 kg/m	7.5 %	50 kN	1000 m
<b>COA018</b>	18 mm	0.240 kg/m	7.5 %	58 kN	1000 m
<b>COA020</b>	20 mm	0.295 kg/m	7.5 %	65 kN	1000 m

#### NOTE

The eyes are available in the following models:  
ALC005 for diameters 08-10 mm  
ALC006 for diameters 12-14 mm  
ALC007 for diameters 16-20 mm

If 2 eyes are needed, 2 ALC have to be ordered.