

RB

FOUR OR FIVE BUNDLED CONDUCTORS BALANCING HEAD BOARDS

RF

FOUR OR FIVE BUNDLED CONDUCTORS FIXED HEAD BOARDS



RB

MODEL	DIMENSIONS [MM]				WORKING LOAD [kN]	WEIGHT [kg]	FOR STRINGING BLOCKS STANDARD	EQUIPMENT		PHASE TYPE	NOTE	
	A	B	C	D				SWIVEL JOINTS				STEEL ROPE SECTION Ø 18
								GGT020	GGT030			
RBQ650	109	218	453	170	93	180	CAQ527 CAQ701	4	1	No. 2-30 m	4 conductors	
RBQ640	109	218	453	170	93	185		5	1	No. 2-30 m No 1-15 m	5 conductors	balan. 1-3

RF

MODEL	DIMENSIONS [MM]				WORKING LOAD [KN]	WEIGHT [KG]	FOR STRINGING BLOCKS STANDARD	EQUIPMENT		PHASE TYPE	
	A	B	C	D				SWIVEL JOINTS			STEEL ROPE SECTION Ø 18
								GGT020	GGT030		
RFQ620	109	218	453	170	93	115	CAQ527 CAQ701	4	1	No. 4-3.5 m	4 conductors
RFP630	109	218	453	170	93	125		5	1	No. 5-3.5 m	5 conductors

CHARACTERISTICS

Specifically designed to connect the pulling rope, max 24 mm diameter, with 2 or 3 bundled conductors.

The equipment includes the necessary rope lengths and swivel joints; quantity and models are indicated in the following tables.

Special models with different characteristics are available on demand.

