

516 SA1T/7

Base unit with 7 drawers

- Oil-proof rubber mats inside

- Centralized locking system

part SER.SBN1

- Drawer handles i high resistant ABS

- Fully opening drawers on telescopic ball bearing slides

- Opportunity to store 3 modules in each drawer











516 SA/2T

Base unit with 2 doors

- 1 internal shelf adjustable in height (70 mm step), resistant to a load of 50 kg
- Centralized locking system
- Sheet steel casing with epoxy process, colour black RAL 9005
- Possibility of mounting lateral accessories such as waste holder 519 RA1, bottle holder 519 RA5, document holder 519 RA2, roll holder 519 RA4
- Possibility to use the raising support 516 SA11T, to increase height up to 1006 mm (including worktop)
- Possibility to use the adjustable feet 516 SA/15 when the floor is not perfectly level

LxDxH mm	∎ Kg	code 📻	
725x505x817	33	U05160252 1	

- Drawers can be equipped with separators 519 SB
- Maximum loading capacity: 1,000 kg
- Possibility to use the raising support 516 SA11T, to increase height up to 1006 mm (including worktop)

- Sheet steel casing and drawers with epoxy process, colour black RAL 9005

- Possibility to use the adjustable feet 516 SA/15 when the floor is not perfectly level

- Possibility of mounting lateral accessories of 516 AC series (from 516 AC1 to 516 AC8)

- Supplied with bottle holder system that can be positioned on the right or left side - spare

- Drawer loading capacity: 20 kg for drawers h 60 mm, 25 kg for drawers h 130 mm and 30 kg for drawer h 200 mm
- Inside dimensions of the drawers:
 5 drawers 570x420x60 mm
- 2 drawer 570x420x130 mm
- 1 drawer 570x420x200 mm

LxDxH mm	i Kg	code 🗾	
725x505x817	55	U05160284 1	



516 SA/16

START roller cabinet - 6 drawers (empty)

- Ideal to be used in combination with the workshop furniture line 516
- Worktop in high resistance ABS
- Double front carrying handle for greater maneuverability
- Fully opening drawers on telescopic ball bearing slides
- Opportunity to store 3 modules in each drawer
- Drawer handles in high resistance ABS
- Oil-proof rubber mats inside
- Centralized locking system
- 4 swivelling oil-proof rubber wheels (Ø 125 mm), two with brakes
- Sheet steel casing and drawers with epoxy process, colour black RAL 9005

∎ Kg

59

- Maximum loading capacity: 800 kg
- Max drawer loading capacity: 40 kg
- Inside dimensions of the drawers:
- 3 drawers 570x420x60 mm
- 2 drawers 570x420x130 mm
- 1 drawer 570x420x200 mm

code U05160266







516 SA17T

Base unit with bin and paper roll holder

- Recycle bin fitted with 2 pair of ball bearing slides: 75 liters capacity 30kg load resistance
- Dedicated compartment for roll of paper and equipped with an easy cutting system (roll of paper Ø250 mm maximum)
- Open space for extra storage
- Possibility to use the raising support 516 SA11T, to increase height up to 1006 mm (including worktop)
- Possibility to use the adjustable feet 516 SA/15 when the floor is not perfectly level
- Possibility of mounting lateral accessories of 516 AC series (from 516 AC1 to 516 AC8).
- Structure in epoxy painted, colour black RAL 9005

LxDxH mm	≜ Kg	code	
725x505x817	44	U05160267	1

New item

LxDxH

725x545x972





