



3/4

### 928 D1 3/4" ■ CE

#### Aluminium impact wrench

- Reversible model with double hammer mechanism
- Six power settings for tightening and untightening
- Spare rotor blades (6 pieces): code 31K100021

| characteristics                 | size     |
|---------------------------------|----------|
| Square drive (")                | 3/4      |
| Bolt capacity                   | M24      |
| Max torque (Nm)                 | 1700     |
| Torque in use (Nm min-Max)      | 500÷1050 |
| Strokes per minute              | 790      |
| Free speed (rpm)                | 5700     |
| Average air consumption (l/min) | 193      |
| Recommended air pressure (bar)  | 6,2      |
| Sound level dB(A)               | 98,4 ±3  |
| Sound power dB(A)               | 109,4 ±3 |
| Vibrations (m/s <sup>2</sup> )  | 9,1      |
| Air inlet (")                   | 3/8      |
| Ø hose size (mm)                | 13       |

| LxDxH mm   | kg  | code      |   |
|------------|-----|-----------|---|
| 222x93x233 | 5,6 | U09280015 | 1 |



3/4

### 928 PD1 3/4" ■ CE

#### Impact wrench (composite material frame)

- Reversible model with double hammer, air exhaust through the handle, power regulator
- Ultra-light casing in high-resistant composite material and steel front housing
- Spare rotor blades (6 pieces): code 31K100037

| characteristics                 | size     |
|---------------------------------|----------|
| Square drive (")                | 3/4      |
| Bolt capacity                   | M27      |
| Max torque (Nm)                 | 1950     |
| Torque in use (Nm min-Max)      | 200÷750  |
| Strokes per minute              | 850      |
| Free speed (rpm)                | 6360     |
| Average air consumption (l/min) | 125      |
| Recommended air pressure (bar)  | 6,2      |
| Sound level dB(A)               | 99,1 ±3  |
| Sound power dB(A)               | 110,1 ±3 |
| Vibrations (m/s <sup>2</sup> )  | 10,7     |
| Air inlet (")                   | 3/8      |
| Ø hose size (mm)                | 13       |

| LxDxH mm   | kg  | code      |   |
|------------|-----|-----------|---|
| 221x86x213 | 3,9 | U09280065 | 1 |



1/2

### 929 PC1/C12 ●

#### Assortment with hexagonal sockets and impact wrench in modular box (12 pcs.)

- Plastic box
- Ergonomic integrated handle
- Double metal closing clip
- Empty sheet steel box: code U09290005Q

| pcs | description  | item/size     |
|-----|--|---------------|
| 10  | Impact hexagonal sockets / 10-13-17-18-19-22-24-27-30-32 | 235 1/2 M     |
| 2   | Lock pins  | 235 MCA/4-6   |
| 2   | Safety rings   | 235 MDA/4-6   |
| 1   | Impact extensions  | 236 1/2 M/125 |
| 1   | Magnesium impact wrench                                  | 929 PC1 1/2   |

| LxDxH mm   | code      |   |
|------------|-----------|---|
| 415x283x92 | U09290005 | 1 |



3/4

### 928 DN/S12 ●

#### Assortment with impact wrench in sheet steel case (13 pcs.)

- Closing clip and carrying handle
- The inside tray is studied to be stored in USAG roller cabinet drawers
- Empty bi-colour foam module: code U05191000Q
- Empty sheet steel box: code U06120005Q

| pcs | description  | item/size   |
|-----|--|-------------|
| 8   | Impact hexagonal sockets / 17-19-22-24-27-30-32-36 | 235 3/4 M   |
| 1   | Lock pins  | 235 MCA/8   |
| 1   | Safety rings                                       | 235 MDA/8   |
| 2   | Impact extensions/100-250                          | 236 3/4 M   |
| 1   | Sheet steel box (empty) - size XXL                 | 612 XXL     |
| 1   | Aluminium impact wrench                            | 928 D1 3/4  |
| 1   | Bi-colour foam module (empty)                      | 519 M 928SV |

| LxDxH mm    | kg   | code      |   |
|-------------|------|-----------|---|
| 575x435x217 | 16,5 | U09280016 | 1 |



1/2

### 929 PC1 1/2" ■ CE

#### Magnesium impact wrench

- Magnesium alloy casing: lightweight and powerful
- Aluminum motor housing
- Reversible model with double hammer mechanism
- 3 tightening torque settings, always maximum untightening power
- Inversion and adjustment by Aluminium lever
- Progressive trigger
- Rubber side bumpers
- Balanced weight for maximum comfort
- Soft-touch bi-material handle
- Silencer and air exhaust integrated in the handle
- Spare rotor blades (8 pieces): code 1004755-67

| characteristics                 | size         |
|---------------------------------|--------------|
| Square drive (")                | 1/2          |
| Bolt capacity                   | M16          |
| Max torque (Nm)                 | 1600         |
| Torque in use (Nm min-Max)      | 280÷440      |
| Strokes per minute              | 1300         |
| Free speed (rpm)                | 7000         |
| Average air consumption (l/min) | 172          |
| Recommended air pressure (bar)  | 6,2          |
| Sound level dB(A)               | 93 ±3        |
| Sound power dB(A)               | 104 ±3 dB(A) |
| Vibrations (m/s <sup>2</sup> )  | 6,2          |
| Air inlet (")                   | 1/4          |
| Ø internal hose (mm)            | 10           |

| LxDxH mm   | kg | code      |   |
|------------|----|-----------|---|
| 162x75x212 | 2  | U09290001 | 1 |



### 930 G

#### Lubricating oil for airtools

- For lubrication line or directly on the airtool

| characteristics                     | size |
|-------------------------------------|------|
| Density to 20° (Kg/m <sup>3</sup> ) | 877  |
| Viscosity to 40°C                   | 65   |
| Viscosity to 100°C (cSt)            | 8,7  |
| Viscosity index                     | 110  |
| Freezing point (°C)                 | -23  |

| ml  | code      |   |
|-----|-----------|---|
| 500 | U09300032 | 1 |



### 934 B

#### Male threaded universal quick couplers with balls

- Brass body, Nickel plated, with grip in shock resistant plastic

| thread " | code      |   |
|----------|-----------|---|
| 1/4      | U09340004 | 5 |
| 3/8      | U09340005 | 5 |
| 1/2      | U09340006 | 5 |