



886 A2

Extractor for MERCEDES Common Rail electronic injectors

- It makes easy the extraction operations in cases of difficult access, without damage risk

gr	code	
560	U08860005	1



886 K

Universal kit for diesel Common rail injector removal

- To remove injectors
- BOSCH (GM 2.2L included)
- SIEMENS (PIEZO V2 included)
- DELPHI
- Multiple connection system (inside/outside) for injectors BOSCH
- Supplied in plastic case

LxPxH mm	Kg	code	
600x420x150	11	U08860010	1



1/2

886 RA

Sockets for removal of diesel injector electric connections

- Hexagonal opening

mm		code	
25	Siemens	U08860005Q	1
27	Siemens	U08860006Q	1
29	Bosch	U08860007Q	1
30	Bosch	U08860008Q	1



886 RB10

Hexagonal bit 10 mm for electrode removal

- Hole Ø 7,5 mm

mm	L mm	code	
10	75	U08860009Q	1



889 F 230

Fluorescent inspection lamp

- Reinforced structure shock-resistant
- Resistant to products and solvents used in car repair garages and industries (DOT, engine oil, gasoline, diesel ...)
- No overheating during operation
- 2 swivelling and adjustable hooks
- 2 Magnets in the rear side

characteristics	size
Light source	FLUO 11 W
Light flux (lm)	320
Light intensity (lux@0,5m)	470
Lamp protection level	IP55
Supply voltage (V)	230
Cable length (m)	10
Cable type	H05 RN-F
Operating temperature (°C)	-20 ÷ 40

LxPxH mm	gr	code	
380x56x44	450	U08890007	1



889 KB

Cable reel with inspection lamp

- Model with automatic cable rewind with roller guide
- Cable stop can be inserted every 50 cm
- Shock resistant body with swivelling bracket for attachment to wall
- Polypropylene structure with bimaterial handle
- Cable sheathed in neoprene
- Supplied without bulb

characteristics	size
Light source	FLUO E27
Power max (W)	15
Lamp protection level	IP65
Cable reel protection level	IP42
Cable length (m)	15
Cable type	H05 RN-F
Supply voltage (V)	230

LxPxH mm	gr	code	
375x290x175	4,0	U08890005	1



NEW

889 LTE

Frontal LED lamp

- Motion sensor to switch the lamp on and off without touching it
- Two brightness levels selectable
- High resistance plastic body
- Edge bumper
- Can also be used with protective helmets
- Adjustable
- Removable, adjustable elastic band

characteristics	size
Light source	1 x COB LED
N° lighting modes	2
Light flux (lm)	50-200
Light beam distance (m)	45-90
Protection level	IP54
Shock resistance	IK05
Battery type (supplied)	3 x 1,5V AAA
Autonomy min-max (hours)	24-6,5
Working temperature (°C)	-20 ÷ +70

gr	code	
100	U08890014	1



889 RA

LED pocket pen lamp

- Hanging clip
- Magnetic base
- Optional strap with additional magnet
- Switch button
- Shock resistant plastic body

characteristics	size
Light source	1 x LED
Light intensity (lux@0,5m)	100
Light flux (lm)	36
Protection level	IP54
Battery type (supplied)	3 x 1,5V AAA
Autonomy (hours)	11

L mm	gr	code	
120	115	U08890031	1