



889 TM

Pen-type LED torch in Aluminium - 170 Lumen

- Anodised Aluminium body
- Built-in front glass
- 3 lighting modes: high-medium-strobe
- Hanging clip
- Switch on with back button

characteristics	size
Light source	1 x SMD LED
N° lighting modes	3
Light flux (lm)	170-55-Strobo
Color temperature (k)	6500
Light beam distance (m)	80
Protection level	IP54
Battery type (not supplied)	2 x AA
Autonomy min-max (hours)	1,5-3
Operating temperature (°C)	-20 ÷ +50

LxPxH mm	g	code	
152x24x24	64	U08890071	1



889 TR

Rechargeable LED torch in Aluminium - 600 Lumen

- Anodised Aluminium body
- Built-in front glass
- 3 lighting modes: high-medium-strobe
- Switch on with back button
- Check of charge status with warning light on lamp (red: charging in progress, green: charge complete)
- Supplied with USB cable

characteristics	size
Light source	1 x SMD LED
N° lighting modes	3
Light flux (lm)	600-200-Strobo
Color temperature (k)	6500
Light beam distance (m)	250
Protection level	IP54
Battery type (supplied)	3,7V Li-Ion 2200 mAh
Autonomy min-max (hours)	2-5
Recharge time (hours)	6
Working temperature (°C)	-20 ÷ +50

LxPxH mm	g	code	
156x40x26	170	U08890073	1



889 TRQ

Spare battery

- For lamp 889 TR

code	
U08890073Q	1



889 TL

LED torch in Aluminium - 680 Lumen

- Anodised Aluminium body
- Built-in front glass
- 3 lighting modes: high-medium-strobe
- Adjustable zoom function
- Switch on with back button

characteristics	size
Light source	1 x SMD LED
N° lighting modes	3
Light flux (lm)	680-190-Strobo
Color temperature (k)	7500
Light beam distance (m)	250
Protection level	IP54
Battery type (not supplied)	3 x C
Autonomy min-max (hours)	6-15
Operating temperature (°C)	-20 ÷ +50

LxPxH mm	g	code	
213x40x31	210	U08890072	1



889 TE

Rechargeable LED torch - dual use

- Dual use: inspection lamp or torch
- Resistant to water and dust
- Hanging clip
- Check of charge status with warning light on lamp body (red: charging, green: charge completed)
- Supplied with wall type charger with USB output

characteristics	size
Light source (lamp function)	1 x 1.3W COB LED
Light source (torch function)	1 x 1.3W SMD LED
Light intensity: lamp-torch (lux@0,5m)	280-180
Light flux: lamp-torch (lm)	110-70
Beam angle: lamp-torch	110°-65°

Protection level	IP54
Shock resistance	IK06
Battery type (supplied)	3.7V Li-poly 750 mAh
Autonomy: lamp-torch (ore)	2,5-3
Recharge time (hours)	2,5
Working temperature (°C)	-10 ÷ +40
Battery charger (INPUT)	AC 100-240V 50/60HZ 5W
Battery charger (OUTPUT)	DC 5.0V 1A

L mm	g	code	
180	85	U08890018	1



889 UB

Rechargeable under bonnet LED inspection lamp

- Ideal to illuminate the engine compartment and the passenger compartment of a car or a commercial vehicle
- Aluminium frame with rubber coated self-locking hooks
- ABS handle
- Supplied with cigarette lighter and battery charger with light (red: charging, green: charge complete)

characteristics	size
Extension: min-max (mm)	1270÷2100
Light source	88 x SMD LED
Light intensity (lux@0,5m)	700
Light flux (lm)	800
Beam angle	120°
Protection level	IP44
Shock resistance	IK07
Battery type (supplied)	7,4 V Li-Ion 2600 mAh
Autonomy (hours)	3/4
Recharge time (hours)	4/5
Operating temperature (°C)	-20 ÷ +50
Battery charger (INPUT)	AC100-240V 50/60 Hz 1.0A Max
Battery charger (OUTPUT)	8.4V 1A

LxPxH mm	g	code	
1270x90x175	2	U08890034	1



889 UC

Spare charger 230 V

- For lamps 889 RD, 889 RF, 889 RUV and 889 UB
- Can be used also with lamp 889 RC (models up to 2016)

code	
U08890032Q	1



890

Battery tester

- For measuring battery charge (6 and 12 V), with turned-off engine, with results within 5 sec
- Allows to check the functioning of the alternator

g	code	
540	U08900001	1