



916 B2

Air drill (10 mm)

- Non-reversible pistol-grip model with self-locking chuck, air exhaust through the handle and variable-speed trigger regulator
- Spare rotor blades (4 pieces): code V.103MFSAV17

| characteristics | size |
|---------------------------------|---------|
| Power (Kw) | 0,45 |
| Free speed (rpm) | 2800 |
| Average air consumption (l/min) | 124 |
| Reccomended air pressure (bar) | 6,2 |
| Sound level dB(A) | 87,4 ±3 |
| Sound power dB(A) | 98,4 ±3 |
| Vibrations (m/s ²) | 7,20 |
| Air inlet (") | 1/4 |
| Ø hose size (mm) | 10 |

| LxPxH mm | kg | code | |
|------------|------|-----------|---|
| 234x44x145 | 1,45 | U09160012 | 1 |



916 B4

by

Right angle air drill (10 mm)

- Reversible model with pistol grip, air exhaust through the handle and variable-speed trigger
- Spare rotor blades (5 pieces): code 1004726-25

| characteristics | size |
|---------------------------------|-------|
| Capacity (mm) | 10 |
| Power (Kw) | 0,35 |
| Free speed (rpm) | 1200 |
| Average air consumption (l/min) | 113 |
| Sound level dB(A) | 84 ±3 |
| Sound power dB(A) | 93 ±3 |
| Air inlet (") | 1/4 |
| Ø hose size (mm) | 10 |
| Reccomended air pressure (bar) | 6,2 |
| Vibrations (m/s ²) | 0,5 |

| LxPxH mm | kg | code | |
|------------|----|-----------|---|
| 200x44x119 | 1 | U09160015 | 1 |



916 C3

by

Air-drill (13 mm)

- Reversible model with pistol grip, air exhaust through the handle and variable-speed trigger
- Composite material body
- Spare rotor blades (5 pieces): code 1004726-87

| characteristics | size |
|---------------------------------|-------|
| Capacity (mm) | 13 |
| Chuck capacity | 1/2 |
| Power (W) | 360 |
| Free speed (rpm) | 400 |
| Average air consumption (l/min) | 80 |
| Reccomended air pressure (bar) | 6,2 |
| Sound level dB(A) | 87 ±3 |
| Sound power dB(A) | 98 ±3 |
| Vibrations (m/s ²) | 4,5 |
| Air inlet (") | 1/4 |
| Ø hose size (mm) | 10 |

| LxPxH mm | kg | code | |
|------------|-----|-----------|---|
| 192x42x151 | 1,3 | U09160016 | 1 |



916 B3

by

Air drill (10 mm)

- Reversible model with pistol grip, self-locking chuck, air exhaust through the handle and variable-speed trigger
- Composite material body
- Spare rotor blades (5 pieces): code 1004725-91

| characteristics | size |
|---------------------------------|-------|
| Capacity (mm) | 10 |
| Power (Kw) | 0,5 |
| Free speed (rpm) | 1800 |
| Average air consumption (l/min) | 113 |
| Reccomended air pressure (bar) | 6,2 |
| Sound level dB(A) | 84 ±3 |
| Sound power dB(A) | 93 ±3 |
| Vibrations (m/s ²) | 0,4 |
| Air inlet (") | 1/4 |
| Ø hose size (mm) | 10 |

| LxPxH mm | kg | code | |
|------------|----|-----------|---|
| 195x151x42 | 1 | U09160014 | 1 |



916 C2

Air drill (13 mm)

- Non-reversible pistol-grip model with self-locking chuck, air exhaust through the handle and variable-speed trigger
- Supplied with additional handle
- Spare rotor blades (4 pieces): code V.97FSAV17

| characteristics | size |
|---------------------------------|--------|
| Capacity (mm) | 0,5÷13 |
| Chuck capacity | 3/8 |
| Power (Kw) | 0,45 |
| Free speed (rpm) | 1300 |
| Average air consumption (l/min) | 124 |
| Reccomended air pressure (bar) | 6,2 |
| Sound level dB(A) | 87 ±3 |
| Sound power dB(A) | 98 ±3 |
| Vibrations (m/s ²) | 6,9 |
| Air inlet (") | 1/4 |
| Ø hose size (mm) | 10 |

| LxPxH mm | kg | code | |
|-------------|-----|-----------|---|
| 280x182x145 | 1,9 | U09160013 | 1 |



918 B

Hammer with hexagonal attachment

- Model with adjustable speed and variable-speed trigger, with connection for chisels with hexagonal shank 918 BH

| characteristics | size |
|---------------------------------|----------|
| Ø shank (mm) | 10 |
| Strokes per minute | 3000 |
| Piston stroke (mm) | 67 |
| Average air consumption (l/min) | 90 |
| Reccomended air pressure (bar) | 6,2 |
| Sound level dB(A) | 102,6 ±3 |
| Sound power dB(A) | 113 ±3 |
| Vibrations (m/s ²) | 8,01 |
| Air inlet (") | 1/4 |
| Ø hose size (mm) | 10 |

| LxPxH mm | kg | code | |
|------------|-----|-----------|---|
| 171x50x160 | 1,6 | U09180006 | 1 |