



3/4

928 DN/S12

Assortment with impact wrench in sheet steel case (13 pcs.)

- Closing clip and carrying handle
- The inside tray is studied to be stored in USAG roller cabinet drawers
- Empty bi-colour foam module: code U05191000Q
- Empty sheet steel box: code U06120005Q

pcs	description	item/size
1	Aluminium impact wrench	928 D1 3/4
8	Impact hexagonal sockets / 17-19-22-24-27-30-32-36	235 3/4 M
1	Lock pins	235 MCA/8
1	Safety rings	235 MDA/8
2	Impact extensions/250	236 3/4 M
1	Bi-colour foam module (empty)	519 M 928SV
1	Sheet steel box (empty) - size XXL	612 XXL

LxPxH mm	kg	code	
575x435x217	16,5	U09280019	1



3/4

928 DN/S19

Assortment with impact wrench in sheet steel case (19 pcs.)

- Closing clip and carrying handle
- The inside tray is studied to be stored in USAG roller cabinet drawers
- Empty bi-colour foam module: code U05191000Q
- Empty sheet steel box: code U06120005Q

pcs	description	item/size
1	Aluminium impact wrench	928 D1 3/4
8	Impact hexagonal sockets / 17-19-22-24-27-30-32-36	235 3/4 M
7	Long impact hexagonal sockets with thin walls /22-24-27-30-32-33-36	235 3/4 MLS
1	Lock pins	235 MCA/8
1	Safety rings	235 MDA/8
2	Impact extensions/250	236 3/4 M
1	Sheet steel box (empty) - size XXL	612 XXL

LxPxH mm	kg	code	
565x415x45	21	U09280021	1



3/4

928 PD1 3/4" ■ CE

Impact wrench (composite material frame)

- Reversible model with double hammer, air exhaust through the handle, power regulator
- Ultra-light casing in high-resistant composite material and steel front housing
- Spare rotor blades (6 pieces): code 31K100037

characteristics	size
Square drive (")	3/4
Bolt capacity	M27
Max torque (Nm)	1950
Torque in use (Nm min-Max)	200÷750
Strokes per minute	850
Free speed (rpm)	6360
Average air consumption (l/min)	125
Recommended air pressure (bar)	6,2
Sound level dB(A)	99,1 ±3
Sound power dB(A)	110,1 ±3
Vibrations (m/s ²)	10,7
Air inlet (")	3/8
Ø hose size (mm)	13

LxPxH mm	kg	code	
221x86x213	3,9	U09280065	1



1/2



929 PC1 1/2" ■ CE

Magnesium impact wrench

- Magnesium alloy casing: lightweight and powerful
- Aluminum motor housing
- Reversible model with double hammer mechanism
- 3 tightening torque settings, always maximum untightening power
- Inversion and adjustment by Aluminium lever
- Progressive trigger
- Rubber side bumpers
- Balanced weight for maximum comfort
- Soft-touch bi-material handle
- Muffler and air exhaust integrated in the handle
- Spare rotor blades (8 pieces): code 1004755-67

characteristics	size
Square drive (")	1/2
Bolt capacity	M16
Max torque (Nm)	1600
Torque in use (Nm min-Max)	280÷440
Strokes per minute	1300
Free speed (rpm)	7000
Average air consumption (l/min)	172
Recommended air pressure (bar)	6,2
Sound level dB(A)	93 ±3
Sound power dB(A)	104 ±3 dB(A)
Vibrations (m/s ²)	6,2
Air inlet (")	1/4
Ø internal hose (mm)	10

LxPxH mm	kg	code	
162x75x212	2	U09290001	1



NEW

1/2

929 PC1/C12

Assortment with hexagonal sockets and impact wrench in modular box (12 pcs.)

- Plastic box
- Ergonomic integrated handle
- Double metal closing clip
- Empty sheet steel box: code U09290005Q

pcs	description	item/size
1	Magnesium impact wrench	929 PC1 1/2
10	Impact hexagonal sockets / 10-13-17-18-19-22-24-27-30-32	235 1/2 M
2	Lock pins	235 MCA/4-6
2	Safety rings	235 MDA/4-6
1	Impact extensions	236 1/2 M/125

LxPxH mm	code	
415x283x92	U09290005	1