



### 045 N

#### Tweezers with straight crossed self-locking tips

- Knurled gripping surface
- Stainless steel body
- Polished finish

L mm	code	
160	U00450002	1



### 046

#### Flexible pick-up claw tool

- Retractable 3-arms claw with push-button control

L mm	a ø max mm	code	
360	20	U00460035	1
500	20	U00460050	1
710	20	U00460070	1



### 046 L

#### Magnetic pick-up tool with LED light

- 4-arms claw
- LED light activates and advances with push-button
- Magnetic tip to retrieve small metal pieces
- Flexible rod, Chrome plated steel

characteristics	size
Type and number of LED	1 Power LED
Brightness (lm/tx)	7 / 100
Battery type (supplied)	3 x LR44
Autonomy min-max (hours)	8
Lamp protection level	IP 54
Operating temperature (°C)	-20 ÷ + 50

L mm	opening max ø mm	capacity max Kg	code	
670	17	2	U00460001	1



### 053 N

#### Spring puller

- Hook- and fork-shaped extremities
- Steel body sheathed in PVC

L mm	code	
200	U00530003	1



### 054

#### Pen oiler

- Push-button for precision dosing
- Body in transparent plastic with pocket clip

L mm	capacity cm <sup>3</sup>	code	
140	5	U00540001	1



### 056

#### Rigid mirror

- Plastic body

L mm	ø mm	code	
170	25	U00566001	5



### 056/1

#### Articulated mirror

- Telescopic brass rod with pocket clip

L mm	ø mm	code	
690	38	U00560002	2



### 056 L

#### Telescopic articulated mirror with LED light

- Glass mirror resistant to scratches
- Plastic shock-proof board protection
- 2 LED to avoid shadows on the inspection zone
- Double adjustable articulation
- Extensible stainless steel body
- Antislip handle
- External diameter (frame included): 75 mm
- Internal diameter (mirror): 51 mm

L max mm	L min mm	ø mm	à gr	code	
875	280	51	86	U00560001	1



### 060/100

#### Butane gas soldering iron

- Model complete with spare nozzle and protection cap
- Supplied with thin tip CT-01
- Ignition with Piezo system
- Charge endurance (at medium regulation): 120 minutes
- Charge capacity: 20 ml
- Supplied without gas

power W	temperature max °C	à gr	code	
100	500	140	U00600005	1



### 060 R

#### Spare thin tip

- For soldering irons 060/100

power W	code	
100	U00600011Q	1



### 060 K

#### Kit with butane gas soldering iron

- Supplied with soldering iron 060/100, spare nozzle, protection cap, four different tips and roll of Tin alloy 60/40 with antioxidant

LxPxH mm	à gr	code	
275x170x45	250	U00600008	1



1 2 3 4

### 060 KR

#### Spare tips

- For kit butane soldering iron 060 K

n°	description	code	
1	Thin tip (3,2 mm)	U00600012Q	1
2	Cutting tip	U00600014Q	1
3	Blowing tip	U00600015Q	1
4	Nozzle	U00600018Q	1