

### **Professional Digital Multimeter**

- Measures voltage and current AC/DC, frequency, resistance
- Continuity and diodes test
- Duty cycle indication
- Automatic calibration
- Data-hold
- Relative mode
- Supplied with a pair of insulated tips
- Spare parts (not included in the package): Kit fuses (2 pieces): 711A-F
  Spare tips (2 pieces): 711A-L

size
400÷600
4÷600
400÷10
400÷10
400÷40
40÷100
10÷100
40÷400
600
1x9V


å gr	code	<del></del>
460	U00760003	1



#### **Automotive digital multimeter**

- Measures voltage and current AC/DC, resistance, capacity, temperature
- Continuity and diodes test
- Automatic calibration function
- Data hold
- Duty cycle indication
- Dwell angle/rpm
- Supplied with a pair of insulated tips for battery and thermocouple
- Spare parts (not included in the package): Kit fuses (2 pieces): 711A-F Spare tips (2 pieces): 711A-L

characteristics	size
Direct voltage DC (mV÷V)	400÷600
Alternating voltage AC (V÷V)	4÷600
Direct current DC (µA÷mA)	400÷400
Alternating current AC (µA÷mA)	400÷400
Resistance (Ω÷MΩ)	400÷40
Temperature with K probe	-20°C÷1000°C
DWELL	180° (2 cil) ÷ 45° (8 cil)
Measurement RPM	250÷40000
Overload protection DC/AC (V)	600
Response in frequency Hz	40÷400
Battery type (supplied)	6xAAA





#### Voltage tester

- Tension/continuity test
- Phase/neutral identification

185

- Phase rotation test
- Visible and audible indication
- Tension measuring (12V ÷ 690V)
- Ideal for verifying the absence of voltage on the inverter terminals of hybrid and electric cars
- Supplied with a pair of insulated tips
- Spare parts (not included in the package): Spare tips (2 pieces): 701B-L

characteristics	size
Direct/Alternating voltage DC/AC (mV÷V)	12÷690
Frequency kHz	50÷60
Battery type (supplied)	1x9V
•	

U00760006



### 1000 V

#### 076 HYB **C**€ □

# Digital multimeter for hybrid and electric cars

- Insulation test up to 4000 Mohm at 250V, 500V, 1000 V
- Measures AC/DC voltage and current, resistance, insulation resistance, frequency, diode, continuity
- Acoustic signal when the resistance is less than  $5M\Omega$
- Supplied with pair of tips and contact tip with crocodile clip for insulation test
- Spare parts (not included in the package): Kit fuses (2 pieces): 714 A-F Spare tips (2 pieces): 714A-L

characteristics	size
Direct voltage DC (mV÷V)	400÷600
Alternating voltage AC (mV÷V)	4÷600
Direct current DC (μA÷mA)	40÷400
Alternating current AC (μA÷A)	40÷400
Resistance (Ω÷MΩ)	400÷40
Overload protection DC/AC (V)	690
Response in frequency Hz	4÷100
Battery type (supplied)	6 x 1,5V AA

code	
00760005	1
	<b>code</b> 00760005





## Ammeter

- Current AC/DC
- Manual resetting function
- Low battery indication
- Compatible with multimeters 076 A and 076 F

characteristics	size	
Direct/Alternating current DC/AC (A÷A)	40÷600	
Max jaw opening (mm)	28	
Max voltage (CA rms)	600V	
Response in frequency Hz	50÷60	
Overload protection DC/AC (V)	600	
Battery type (supplied)	1x9V	

<b>å</b> gr	code	•
310	U00760010	1