


191

**Cable cutter for steel cables**

- Model for round steel cables and strands
- PVC handles
- Burnished finish



L mm	≈ 2000 N/mm <sup>2</sup> ø max mm	≈ 1600 N/mm <sup>2</sup> ø max mm	code	
165	1,5	5	U01910001	1



196 N

**Bolt cutters with central cutter**

- Blades with high-resistance cutting edges
- Handgrips in PVC

L mm	≈ 2000 N/mm <sup>2</sup> ø max mm	≈ 1600 N/mm <sup>2</sup> ø max mm	kg	code	
450	6	7	1,9	U01960002	1
600	7	10	3,5	U01960003	1
750	9	13	4,5	U01960004	1
900	10	16	6,1	U01960005	1
1050	11	18	8,3	U01960006	1



196 NR

**Bolt cutters with semi-flush cutter**

- Blades with high-resistance cutting edges
- Handgrips in PVC

L mm	≈ 2000 N/mm <sup>2</sup> ø max mm	≈ 1600 N/mm <sup>2</sup> ø max mm	kg	code	
350	5	6	1,3	U01960001	1



196 AN

**Spare blades**

- For bolt cutters 196 N and 196 NR (size 350 mm)
- Blades supplied with bolts

L mm	code	
R 350	U01960010Q	1
450	U01960020Q	1
600	U01960030Q	1
750	U01960040Q	1
900	U01960050Q	1
1050	U01960060Q	1



199

ISO 9242

**Pincers for cement layers**

- Carbon steel
- Phosphatized finish

L mm	a mm	code	
190	15	U01990010	5
225	17	U01990015	5
250	19	U01990013	5
280	19	U01990150	5



200

**Hacksaw**

- Model for 300 mm blades with adjustable blade
- Screw for regulating blade tension
- Aluminium handle
- Supplied with steel blade

mm blade "	L mm	code	
300 12	450	U02000001	1



200 F

**Aluminium hacksaw with Tension Control**

- Model for 300 mm blades
- Adjustable blade with 8 different positions, every 45° rotation
- Constant tension of the blade built in the handle and calibrated at 110 kg for perfect cuts
- Constant cutting capacity (100 mm)
- Less vibrations
- Aluminium body with bimaterial handle
- Supplied with Cobalt blade 200 C24



mm blade "	L mm	code	
300 12	440	U02006003	1



200 L

**Hacksaw**

- Model for 300 mm blades
- Wooden handle
- Supplied with steel blade

mm blade "	L mm	code	
300 12	500	U02000003	1



200 S

**Hacksaw**

- Model for 300 mm blades with possibility of positioning the blade at 45° and 90°
- Blade tension regulator integrated in the handle
- Steel body with anti-slip and shock resistant plastic coating
- Supplied with Cobalt blade 200 C24

mm blade "	L mm	code	
300 12	385	U02000002	1



200 C/10 PCS

**Spare blade for hacksaw (pack of 10 pcs.)**

- HSS steel with high Cobalt content
- Excellent cut and long blade life

n° teeth	mm blade "	code	
18	300 12	U02000201	1
24	300 12	U02000202	1
32	300 12	U02000203	1



201

**Hacksaw**

- Light model for 150 mm blades
- Steel bow
- Supplied with Super Rapid steel blade (32 teeth per inch)

mm blade "	L mm	code	
150 6	237	U02010001	10



201 S

**Hacksaw with blade tensioner**

- Light model for 150 mm blades
- Supplied with Super Rapid steel blade (32 teeth per inch)

L mm	mm blade "	code	
255	150 6	U02010003	5