

810 N

ISO 6789

Torque wrenches with reversible ratchet

- Adjustable torque model for clockwise tightening
- Accuracy $\pm 4\%$ of the preset torque value
- Readings in Nm
- Sensible and audible alarm on reaching preset torque value
- Automatic resetting on pressure release after disengagement
- Supplied with test certificate

PRECISION
 $\pm 4\%$

1
4"

**CLOCKWISE
TIGHTENING**



ITEM	CODE	CAPACITY	☑	L (mm)	RESOL.
810 N 5	U08104000	1 ÷ 5	1/4"	197	0,05
810 N 25	U08104001	5 ÷ 25	1/4"	290	0,05

811 NE

ISO 6789

Torque wrenches with removable reversible ratchet

- Adjustable torque model for use in combination with fittings from the 811-series
- For clockwise and counterclockwise tightening by turning the fittings 180°
- 9x12 or 14x18 mm fittings
- Accuracy $\pm 4\%$ of the preset torque value
- Readings in Nm
- Sensible and audible alarm on reaching preset torque value
- Automatic resetting on pressure release after disengagement
- Supplied with test certificate
- Complete with reversible ratchet 811 E with 72 teeth

PRECISION
 $\pm 4\%$

1
4"

**CLOCKWISE AND
COUNTERCLOCKWISE
TIGHTENING**



ITEM	CODE	CAPACITY	☑	○	L (mm)	RESOL.
811 NE 5	U08114009	1 ÷ 5	1/4"	9x12	185	0,05
811 NE 25	U08114010	5 ÷ 25	1/4"	9x12	300	0,05

812 N

ISO 6789

Torque wrenches with reversible ratchet

- Adjustable torque model for clockwise and counterclockwise tightening by turning the ratchet 180°
- Accuracy $\pm 4\%$ of the preset torque value
- Readings in Nm
- Sensible and audible alarm on reaching preset torque value
- Automatic resetting on pressure release after disengagement
- Safety block after setting torque
- Supplied in sheet steel box with test certificate
- Ratchet with male square drive 3/4"

PRECISION
 $\pm 4\%$

3
4"

**CLOCKWISE AND
COUNTERCLOCKWISE
TIGHTENING**



ITEM	CODE	CAPACITY	☑	○
812 N 600	U08120006	120 ÷ 600	3/4"	14x18
812 N 1000	U08120010	200 ÷ 1000	3/4"	-

824 A

ISO 6789

Torque screwdrivers

- Adjustable torque model for clockwise tightening, for use in combination with bits from the 660 series or, using an adapter, with sockets from the 1/4" manual series
- Accuracy $\pm 6\%$ of the preset torque value
- Readings in Nm
- Automatic disengagement on reaching the preset torque value
- Automatic resetting after 120°
- Supplied with regulation key and test certificate

1/4"

PRECISION
 $\pm 6\%$

**CLOCKWISE
TIGHTENING**



CODE	CAPACITY	L (MM)	RESOL.
U08240004	0,5 ÷ 2,5	145	0,1
U08240006	2 ÷ 10	167	0,5