

SMART FUNCTION

Automatically selects AC/DC
voltage, resistance,
frequency

MAX
600 V

RMS



074 A

Code U00740001

SMART digital multimeter

- AC/DC measurement
- Resistance and continuity measurements (acoustic sound if circuit resistance is lower than 40 to Ω)
- Frequency measurements
- AC/DC current measurement with 076 P ammeter

TECHNICAL CHARACTERISTICS

Direct voltage DC (mV÷V)	1÷600 mV÷V
Alternating voltage AC (mV÷V)	1÷600 mV÷V
Resistance (Ω ÷M Ω)	0÷10 Ω ÷M Ω
Frequency kHz	3÷40 kHz
Battery type (supplied)	2xAAA 1,5V



CE
CAT III 600V

Ideal on the inverter
terminals of hybrid
and electric cars
(CEI 11-27)

MAX
690 V



076 G

Code U00760006

Voltage tester

- Tension/continuity test
- Phase/neutral identification
- Phase rotation test
- Visible and audible indication



CE

TECHNICAL CHARACTERISTICS

Direct/Alternating voltage DC/AC (mV÷V)	12÷690 mV÷V
Frequency kHz	50÷60 kHz
Battery type (supplied)	1x9V



007 MV

Code U00070035

Tool-holding pouch (empty)

- High strength fabric
- Velcro belt fixing
- Four stretch pockets for tools
- Hook for tape



007 MLV

Code U00070030

Tool-holding pouch with belt (empty)

- High strength fabric
- Six stretch pockets for tools
- Hook for tape
- Adjustable belt from 80 to 120 cm