

LED LIGHTING

1/2"

1.898 Nm

2,2 kg



YouTube

MAGNESIUM ALLOY CASING



THE TOP OF THE RANGE

943 PC1 1/2"

Code U09430001

Magnesium impact wrench with LED - the top

TECHNICAL CHARACTERISTICS	TECHNICAL CHARACTERISTICS
Square drive (")	1/2"
Bolt capacity	M20
Max torque (Nm)	1.898 Nm
Torque in use (Nm min-Max)	320÷460 Nm
Strokes per minute	1200
Free speed (rpm)	6.500 rpm
Average air consumption (l/min)	172 l/min
Recommended air pressure (bar)	6,2 bar
Sound level dB(A)	94 ±3 dB(A)
Sound power dB(A)	105 ±3 dB(A)
Vibrations (m/s ²)	6,4 m/s ²
Air inlet (")	1/4"
Ø internal hose (mm)	10 mm
Weight	2,2 kg

MAGNESIUM ALLOY CASING

1/2"

1.600 Nm

2 kg



YouTube



THE REFERENCE MODEL

929 PC1 1/2"

Code U09290001

Magnesium impact wrench

TECHNICAL CHARACTERISTICS	TECHNICAL CHARACTERISTICS
Square drive (")	1/2"
Bolt capacity	M16
Max torque (Nm)	1.600 Nm
Torque in use (Nm min-Max)	280÷440 Nm
Strokes per minute	1.300
Free speed (rpm)	7.000 rpm
Average air consumption (l/min)	172 l/min
Recommended air pressure (bar)	6,2 bar
Sound level dB(A)	93 ±3 dB(A)
Sound power dB(A)	104 ±3 dB(A)
Vibrations (m/s ²)	6,2 m/s ²
Air inlet (")	1/4"
Ø internal hose (mm)	10 mm
Weight	2,0 kg

EXTRA-COMPACT



942 PC3 1/2"

Code U09420012

Extra-compact impact wrench

TECHNICAL CHARACTERISTICS	TECHNICAL CHARACTERISTICS
Square drive (")	1/2"
Bolt capacity	M16
Max torque (Nm)	861 Nm
Torque range (Nm)	150÷220 Nm
Strokes per minute	1650
Free speed (rpm)	10.000 rpm
Average air consumption (l/min)	127 l/min
Recommended air pressure (bar)	6,2 bar
Sound level dB(A)	91,1±3 dB(A)
Sound power dB(A)	108,1±3 dB(A)
Vibrations (m/s ²)	9,57 m/s ²
Air inlet (")	1/4"
Ø hose size (mm)	10 mm
Weight	1,3 kg

1/2"

861 Nm

1,3 kg



YouTube